* u			PA-IDC	
QUERY CONTROL FORM		RTIS USE ONLY		
Application No. 19/04/757	Prepared by	Lois Stone	Tracking Number	5884451
Examiner-GAU Sement - 1711	Date	2/18/04	Week Date	1504
	No. of queries	`\	~~ FW	

JACKET				
a. Serial No.	f. Foreign Priority	k. Print Claim(s)	p. PTO-1449	
b. Applicant(s)	g. Disclaimer	I. Print Fig.	q. PTOL-85b	
c. Continuing Data	h. Microfiche Appendix	m. Searched Column	r. Abstract	
d. PCT	i. Title	n. PTO-270/328	s. Sheets/Figs	
e. Domestic Priority	j. Claims Allowed	o. PTO-892	t. Other	

SPECIFICATION	MESSAGE
a. Page Missing	Page 11, line 17 of the file refors to canceled claim 35. Please advise.
b. Text Continuity	sanceled slaim 35. Please advise
c. Holes through Data	
d. Other Missing Text	
e. Illegible Text	
f. Duplicate Text	
g. Brief Description	
h. Sequence Listing	
i. Appendix	
j. Amendments	
k. Other	
CLAIMS	
a. Claim(s) Missing	
b. Improper Dependency	Thank you,
c. Duplicate Numbers	
d. Incorrect Numbering	initials હઠ
e. Index Disagrees	RESPONSE In the spee page 11, line 17 Replace claim 35 with claim 12
f. Punctuation	Replace claim 35 with claim /2
g. Amendments	
h. Bracketing	
i. Missing Text	
j. Duplicate Text	
k. Other	
	initials & A

block copolymers include styrene-ethylene/butylene-styrene (SEBS). One preferred thermoplastic elastomer block copolymer is commercially available as Krayton® by Shell Chemical Company.

Specifically, when the diblock copolymer comprises semifluorinated monodendron side chains, the surface active block copolymer (SABC) can have a surface energy of about 8 mN/m to about 20 mN/m. When the diblock copolymer comprises oligoethylene glycol side chains, the surface active block copolymer (SABC) can have a surface energy of about 40 mN/m to about 60 mN/m.

Specifically, when the diblock copolymer comprises semifluorinated monodendron side chains, the surface active block copolymer (SABC) can have a water contact angle of about 100 degrees to about 150 degrees. When the diblock copolymer comprises oligoethylene glycol side chains, the surface active block copolymer (SABC) of claim 35 that has a water contact angle of about 25 degrees to about 60 degrees.

Specifically, when the diblock copolymer comprises semifluorinated monodendron side chains, the thermoplastic elastomer block copolymer can be present in about 1 wt.% to about 20 wt.% of the surface active block copolymer (SABC). When the diblock copolymer comprises oligoethylene glycol side chains, the thermoplastic elastomer block copolymer can be present in about 80 wt.% to about 99 wt.% of the surface active block copolymer (SABC).

Specifically, when the diblock copolymer comprises semifluorinated monodendron side chains, the diblock copolymer can be present in about 2 wt.% to about 5 wt.% of the surface active block copolymer (SABC). When the

03/31/04